

LATAPOXY® STANDARD Epoxy adhesive



Features / Benefits

- Solvent free
- High strength
- Chemical Resistant
- Heat resistant
- Long working time
- Bonds multiple substrates

Application

Engineered especially for Stone installation on stone, wood and other substrates, Stone Cladding, Kitchen Moulding, Staircase Beading, Windows and Door framing, **Technical Data Sheet**



LATAPOXY Standard is a two-component epoxy adhesive specifically formulated to provide exceptionally high bond strength on stone installation over various substrates.

Substrates

- Granite
- Stone
- Ceramic
- Concrete
- Marble
- MetalsWood
- Glass.

TECHNICAL DATA

Properties	Standard Epoxy Adhesive	
	Part-A	Part-B
	(Hardener)	(Resin)
Physical Appearance	Pale yellow	Semi-Transparent
	Viscous liquid	Viscous liquid
Viscosity cP	35000-45000	35000-42000
Curing Properties		
Mixing Ratio (H: R)	80:100 (By weight), 100:100 (By	
	Volume)	
Pot Life (Minutes)	20-30	
Gel Time (Minutes)	60-70	
Shore D	75-80	
Setting Time	5-6 hrs	
Coverage	110-120 sq.ft	
Bond Strength	White marble - 135 kg /sq. cm	
	Metal - 111 kg/sq. cm	
Shelf Life	2 years	

Packaging:

1.8KG (Part A: 800g, Part B: 1kg)450G (Part A: 200g, Part B: 250g)

180G (Part A: 80g, Part B: 100g)

Instructions for use:

- 1. Ensure that the substrates are thoroughly cleaned for dust, grease, and rust.
- 2. Create a textured/rough surface to achieve a maximum bonding effect.
- 3. Pour equal quantities of material from Part-A & Part-B containers.
- 4. Homogeneously mix both parts.
- 5. The pot life is 25-35 minutes @ 25°C.
- 6. Apply a thin layer, on both surfaces using a kind of putty blade.
- 7. Securely clamp the objects on both sides and allow for curing over a period of a minimum of 4-5 hours.

Health and Safety Instructions:

- Use rubber hand gloves, safety goggles, while using Latapoxy Standard Epoxy Adhesive.
- 2. Inhalation: Seek fresh air.
- 3. Ingestion: Washout mouth thoroughly drink water. Seek medical advice if symptoms persist.

- 4. Skin contact: Wash the skin with plenty of water.
- 5. Eye Contact: Flush with water, until irritation subsides. Seek medical advice if symptoms persist.
- 6. Keep out of reach children.

CUSTOMER CARE

MYK LATICRETE India Pvt Ltd.

Plot No. 30/C (Sy. No. 83/1), Orbit Building, 17th Floor, Tower 1, Knowledge City, TSIIC, Raidurgam, Ranga Reddy Dist.,

Hyderabad - 500 081, Telangana, India.

Tel: +91-40-6817 3100

Customer Care: cc@myklaticrete.com

Website: www.myklaticrete.com